

Sub:- Data for 20mm thick chipping carpet

Item No.674

Providing 20mm thick premixed chipping carpet with sand flushing seal cot using departmental materials viz:, 12mm broken stone 0.18m³, 9mm broken stone 0.09m³ and sand 0.09m³ premixed with hot bitumen 21.40 Kg per 10 m² including attack coat of 2.5 kg per 10m² (40 Kg per m³ stone, 90 Kg per m³ of sand) hire for boiler, sprayer, roller, drum mixers, wire brushes, brass brooms, cost of fuel and oils , lighting, waching and sundry stores etc. compete including cost of bitumen.

Details for 100m

0.12 day	Hire for boiler and sprayer ***** day		
0.12 day	Hire for roller		
2.2 lr.	Diesel oil for roller *** litre		
86 Kg.	Fire wood split for heating bitumen		
L.S.	Hire for arum mixers, wire brushes, brass brooms, cost of other oils, lighting, watching and other sundry stores etc.	L.S.	Rs.2.50
Labour			

10.00	Snl.Mazdoors		Each
4.00 Women			-do-
Total			
	Hence for 10m ²		

N.B. In case it is not possible to obtained 9mm broken stone, 12mm broken stone may be used for full quantity of 0.27 m³

(sd)
Chief Engineer